

### **GEOWEB CELLULAR CONFINEMENT SYSTEM**

EMERGENCY NUMBER:

920-739-9471

PRODUCT INFORMATION & PRODUCT APPLICATIONS

800-548-3424

## **SECTION I - IDENTIFICATION**

PRODUCT: GEOWEB

CHEMICAL FAMILY: Polyolefin

PRODUCT DESCRIPTION: Fabricated polymer article

## SECTION II - HAZARDOUS INGREDIENT INFORMATION

This product is not a hazardous chemical as defined in 29 CFR 1910.1200.

### **SECTION III - HEALTH INFORMATION**

- SWALLOWING: No evidence of adverse effects.
- SKIN CONTACT: Molten or heated material can cause serious burns to unprotected skin.
- EYE CONTACT: Particulates and fines may cause mechanical irritation to the eyes.
- INHALATION: Dust can be caused by handling and some operations. Thermal decomposition may generate fumes which may be irritating to the respiratory tract.

#### PRESTO GEOSYSTEMS

670 N PERKINS STREET, APPLETON, WISCONSIN, USA 54914 PH: 920-738-1328 OR 800-548-3424 ■ FAX: 920-738-1222 E-MAIL: INFO@PRESTOGEO.COM WWW.PRESTOGEO.COM



### SECTION IV - OCCUPATIONAL EXPOSURE LIMITS

PEL/TWA (OSHA Permissible Exposure Limit/Time-Weighted Average): No OSHA PEL for this mixture. For particulates not otherwise regulated (dust): 15 mg/m3 for total dust and 5 mg/m3 for respirable dust.

TLV/TWA (ACGIH Threshold Limit Value/Time-Weighted Average): No ACGIH TLV for this mixture. For particulates not otherwise classified (dust): 10 mg/m3 for total dust.

## **SECTION V - EMERGENCY FIRST AID PROCEDURE**

### FOR OVEREXPOSURE BY:

- SWALLOWING: This product is not known to be harmful by oral ingestion.
- SKIN CONTACT: If contacted by molten polymer, immediately flush area with large amounts of water, call for prompt medical attention.
- EYE CONTACT: This product is an inert solid. If in eye, remove as one would any foreign object.
- INHALATION: In case of adverse exposure to fumes formed at elevated temperatures, immediately remove the individual from exposure. If breathing has stopped, give immediate artificial respiration, call for prompt medical attention.

# SECTION VI - PHYSICAL DATA

BOILING POINT MELTING POINT:

VAPOR PRESSURE: SPECIFIC GRAVITY: VAPOR DENSITY (AIR = 1): SOLUBILITY IN WATER: APPEARANCE AND ODOR: Does not apply. 250-270° F (121-132° C) Does not apply. 0.91 to 0.96 g/cc Does not apply. Insoluble Black polymer article, no odor

#### PRESTO GEOSYSTEMS

670 N PERKINS STREET, APPLETON, WISCONSIN, USA 54914 PH: 920-738-1328 OR 800-548-3424 ■ FAX: 920-738-1222 E-MAIL: INFO@PRESTOGEO.COM WWW.PRESTOGEO.COM



## SECTION VII - FIRE AND EXPLOSION HAZARDS

FLASH POINT & METHOD USED:	Does not apply.
AUTO-IGNITION TEMPERATURES:	Does not apply.
FLAMMABLE LIMITS IN AIR, % BY VOL.	LOWER: Does not apply. UPPER: Does not apply.

FIRE FIGHTING PROCEDURES: (Note: Individuals should perform only those fire-fighting procedures for which they have been trained.) Use water spray, dry chemical, foam, or carbon dioxide. Respiratory and eye protection required for fire-fighting personnel.

UNUSUAL FIRE & EXPLOSION HAZARDS: Combustion may produce carbon monoxide and irritating smoke.

# SECTION VIII - REACTIVITY

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS & MATERIALS TO AVOID: May burn or react violently with fluorine/oxygen mixtures. May be decomposed by strong oxidizing agents such as nitric and sulfuric acids, and chlorinating agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition products may include CO, CO2, and organic vapors.



## **SECTION IX - EMPLOYEE PROTECTION**

VENTILATION: Engineering controls should be used whenever feasible to maintain concentrations below dust exposure limits (Section IV), including but not limited to enclosures, local ventilation and dilution ventilation. Provide adequate ventilation at locations where polymer is at elevated temperatures.

RESPIRATORY PROTECTION: Where engineering controls are not feasible or sufficient to achieve full conformance with dust exposure limits (Section IV), use NIOSH/MSHA approved respiratory protection equipment.

PROTECTIVE CLOTHING: Generally, no need anticipated. Wear heat protective gloves and clothing if there is potential contact with heated material.

EYE PROTECTION: If necessary, wear safety glasses meeting specifications of ANSI Standard Z87.1

# SECTION X - ENVIRONMENTAL PROTECTION

WASTE DISPOSAL: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. This product, if disposed in its pure state, is not a RCRA hazardous waste.

#### **PRESTO GEOSYSTEMS**

670 N PERKINS STREET, APPLETON, WISCONSIN, USA 54914 PH: 920-738-1328 OR 800-548-3424 ■ FAX: 920-738-1222 E-MAIL: INFO@PRESTOGEO.COM WWW.PRESTOGEO.COM



## **SECTION XI - REGULATORY CONTROLS**

DEPARTMENT OF TRANSPORTATION:

DOT CLASSIFICATION:Non-regulated commodityDOT PROPER SHIPPING NAME:Non-regulated commodityOTHER DOT INFORMATION:Non-regulated commodity

OTHER REGULATORY REQUIREMENTS:

Toxic Substance Control Act:

The components of this product are listed in the TSCA Inventory of Chemical Substances.

SARA Title III (Sections 311/312) Hazard Categories:

This product does not meet the criteria of any SARA hazard categories.

### SECTION XII - STORAGE AND HANDLING

ELECTROSTATIC ACCUMULATION HAZARD: Use proper grounding procedure

STORAGE TEMPERATURE (F): STORAGE PRESSURE (mmHg): LOADING TEMPERATURE (F): LOADING VISCOSITY (cSt @ F):

Ambient Atmospheric Not applicable Not applicable

The information contained herein is based on data available to us and is believed to be correct. However, Presto Products makes no warranty regarding the accuracy or completeness of this information, and assumes no legal responsibility for the use of this information.

PREPARED BY: RAM

REVISION DATE: June 30, 1997

SUPERSEDES: Jan. 3, 1997

PRESTO GEOSYSTEMS 670 N PERKINS STREET, APPLETON, WISCONSIN, USA 54914 PH: 920-738-1328 OR 800-548-3424 ■ FAX: 920-738-1222 E-MAIL: INFO@PRESTOGEO.COM WWW.PRESTOGEO.COM